




Introducing the

DT light Series

Manual dissolution testing, simple and compact



Manual dissolution testing, simple and compact

DT light Series

The ERWEKA DT light Series delivers the proven ERWEKA quality in a comprehensive package for a budget for simple dissolution testing with USP method 1, 2, 5 and 6. The DTs are equipped with 6 or 8 test stations and a fixed drive head (high-head), allowing easy access to each 1000 ml vessel.

The shafts can be replaced easily and the unique water bath of moulded PET is equipped with the time-proven ERWEKA water outlet for easy cleaning. The external flow through heater reduces the influence of external vibrations and ensures a constant temperature. Every accessory that comes into contact with the dissolution sample is installed in Germany. Therefore our DT light Series has the ERWEKA made in Germany quality.

All these features make sure that the ERWEKA DT light Series is the perfect entry-level device for the world of dissolution testing.

Highlights

- 100 % USP/EP/JP compliant
- Compact design saving lab space
- High-head mode for easy access to the vessels
- Universal shafts with attachments for Method 1, 2 (paddles included), 5 and 6 available
- Easy cleaning of the water bath and the set-up area
- External flow through heater reduces influence of external vibrations and ensures constant temperature
- Simple control using symbol keypad with LED display for temperature, RPM and runtime
- Manual sampling using height adjustable holder for USP sampling points

Technical Data

USP methods 1 (Basket), 2 (Paddle), 5 (Paddle over Disk) and 6 (Rotation Cylinder) with 6 or 8 test stations – USP method 2 included

100 % USP/EP/JP compliant

Fulfills all specifications in accordance with FDA “Mechanical Calibration”

USB-A printer interface (for selected printers)

USB-B interface for firmware updates

RS 232 interface for heater control

External PT 100 temperature sensor

Rotational speed 20 - 250 rpm

Heating range: 30 - 50 °C (± 0,2 °C)



LED display and symbol keypad for easy control




Low-evaporation vessel covers are included

DT 126 light

Specifications


- High-head with 6 test stations
- Dimensions (width / depth / height): 510 mm / 450 mm / 660 mm
- Weight: 30 kg



DT 128 light

Specifications

- High-head with 8 test stations
- Dimensions (width / depth / height): 642 mm / 482 mm / 680 mm
- Weight: 38 kg





Contact

Are you curious and want to find out more?
Head over to our website and download our product brochures,
watch videos of our equipment in action or find the ERWEKA
dealer of your country.



E-Mail: sales@erweka.com
Phone: +49 6103 92426-200
Fax: +49 6103 92426-999



support@erweka.com



www.erweka.com



spareparts@erweka.com



www.facebook.com/erweka.gmbh

ERWEKA GmbH

Pittlerstr. 45
63225 Langen
Germany

E-Mail: sales@erweka.com
Phone: +49 6103 92426-200
Fax: +49 6103 92426-999

Technical specifications of products described are
stated without warranty and subject to change at
any time without further notice. v.1.2.1.23

ERWEKA light